WHEN SAFETY COMES FIRST SPRAYDRENCH® EMERGENCY SAFETY SHOWERS

EW 111 ST



Detailed Description

Free-Standing Platform Operated Eye/Face Wash Station c/w Twin Aerator Nozzle with Dust Caps

Best Suited Applications

- Low risk areas
- Laboratories
- General manufacturing
- Applications where only an eyewash is required
- School/University low risk laboratories
- High dust areas

Inlet: 1/2" BSP(F)
Outlet: 1/2" BSP(M)

Eyewash: Twin Aerator Nozzles 20 lpm

Flow Rates at design pressure of ± 2.5 bar(g)

Eye Wash Free Standing Stainless Steel Foot Operated Eyewash EW 111 S T

Additional Info.

Material of Construction Stainless Steel

Approx. Floor Foot Print (cm) ± 80 (L) x50 (W) x100 (H)

Single Unit Weight (kg) ± 15

Typ. Single Unit Pack Dim. (cm) ± 90 (L) x 60 (W) x 110 (H)

All SPRAYDRENCH® products are manufactured according to the following standards:

ANSI Z358.1-2014 DIN 12899-3:2008 EN15154-1:2006-12 EN15154-2:2006-12 EN15154-5:2019-12

Further Detail Available on Request

TEL: +27 (0)11 466 2100 | FAX: +27 (0)11 466 0618



sales@spraynozzle.co.za

PO BOX 2369, HALFWAY HOUSE, SOUTH AFRICA, 1685 | REG:1971/014137 WWW.SPRAYDRENCH.CO.ZA | WWW.SPRAYNOZZLE.CO.ZA

