

WHEN SAFETY COMES FIRST
SPRAYDRENCH[®]
 EMERGENCY SAFETY SHOWERS

MO 000 S



SPRAYDRENCH[®]
 EMERGENCY SAFETY SHOWERS

Detailed Description

Wall Mounted Safety Shower Only

Optional Extras

- Scald &/or Freeze Protection Valve
- Additional Options Available on Request

Best Suited Applications

- Low risk areas
- Laboratories
- Laboratory corridors
- School/University low risk laboratories
- Workshops
- Fuel load/offloading

Inlet : 3/4" BSP(F)

Primary Shower Nozzle (1 off SD34DN)
 85 lpm

Flow Rates at design pressure of ±2.5 bar(g)

Additional Info.

Material of Construction Stainless Steel

Approx. Floor Foot Print (cm) ±55 (L) x20 (W) x65 (H)

Single Unit Weight (kg) ±6

Typ. Single Unit Pack Dim. (cm) ±65 (L) x 30 (W) x 75 (H)

All **SPRAYDRENCH**[®] products are manufactured according to the following standards:

ANSI Z358.1-2014
 DIN 12899-3:2008

EN15154-1:2006-12
 EN15154-2:2006-12
 EN15154-5:2019-12

Further Detail Available on Request

Manually Operated
 Wall Mounted
 Stainless Steel

MO 000 S

TEL: +27 (0)11 466 2100

spray nozzle (PTY) LTD

sales@spraynozzle.co.za

PO BOX 2369, HALFWAY HOUSE, SOUTH AFRICA, 1685 | REG:1971/014137
 WWW.SPRAYDRENCH.CO.ZA | WWW.SPRAYNOZZLE.CO.ZA

SPRAYDRENCH[®]
 EMERGENCY SAFETY SHOWERS