

WHEN SAFETY COMES FIRST  
**SPRAYDRENCH**<sup>®</sup>  
 EMERGENCY SAFETY SHOWERS

PO 011 EH



Detailed Description

Epoxy-Coated Mild Steel Platform Operated Single Column Drench Shower c/wHand/ Push Operated Rigid Emergency Eyewash Station c/w Twin Aerator Nozzle with Dust Caps

Optional Extras

- Scald &/or Freeze Protection Valve
- Shower Support
- Additional Options Available on Request

Best Suited Applications

- Moderate risk areas
- Battery charging areas
- Dipping operations
- Sample points
- Mining general processing
- Laboratories
- Fuel load/offloading

Inlet : 1" BSP(M)

Primary Shower Nozzle (1 off SD10DN-PP)

85 lpm

Secondary Shower Nozzle (1 off SD12DN BR)

31 lpm

Eyewash: Twin Aerator Nozzles

20 lpm

Flow Rates at design pressure of  $\pm 2.5$  bar(g)

- Platform Operated
- Single Column Free Standing
- Epoxy Coated Carbon Steel
- Hand Operated Eye Wash

PO 011 EH

Additional Info.

Material of Construction Epoxy Coated Carbon Steel  
 Approx. Floor Foot Print (cm)  $\pm 105$  (L) x  $110$  (W) x  $235$  (H)  
 Single Unit Weight (kg)  $\pm 26$   
 Typ. Single Unit Pack Dim. (cm)  $\pm 157$  (L) x  $74$  (W) x  $34$  (H)

All **SPRAYDRENCH**<sup>®</sup> products are manufactured according to the following standards:

ANSI Z358.1-2014  
 DIN 12899-3:2008

EN15154-1:2006-12  
 EN15154-2:2006-12  
 EN15154-5:2019-12

Further Detail Available on Request

TEL: +27 (0)11 466 2100 | FAX: +27 (0)11 466 0618

**spray nozzle** (PTY) LTD

sales@spraynozzle.co.za

PO BOX 2369, HALFWAY HOUSE, SOUTH AFRICA, 1685 | REG:1971/014137  
 WWW.SPRAYDRENCH.CO.ZA | WWW.SPRAYNOZZLE.CO.ZA

